



# PART NUMBERING SYSTEM

## CRYSTAL UNITS

### Through Hole Crystal Units Part Numbering System

E ↓ Internal Code	UA	3.57954	F	20	A	3	3	L
Package	Nominal Frequency (In MHz)	Vibration Mode	Load Capacitance	Operating temperature Range	Frequency Tolerance	Frequency Stability	Option (can be blank)	
UA=HC-49U SA=HC-49SA SC=HC-49SB MA=UM-1 MB=UM-5 AT=AT-39	Please enter the nominal frequency (7 digitals include the decimal)	F=AT-Fund T=AT-3 <sup>RD</sup> V=AT-5 <sup>TH</sup> B=BT-Fund	00=series 10=10pF 32=32pF (Pls enter the value of load capacitance)	A=0°C to +50°C B=0°C to +70°C C=-10°C to +60°C D=-10°C to +70°C E=-20°C to +70°C M=-40°C to +85°C N=-40°C to +105°C R=-55°C to +125°C S=Others	1=±10ppm 2=±20ppm 3=±30ppm 5=±50ppm 0=±100ppm X=±5ppm Y=±15ppm Z=±25ppm	1=±10ppm 2=±20ppm 3=±30ppm 5=±50ppm 0=±100ppm X=±5ppm Y=±15ppm Z=±25ppm	L=Cut Lead S=Insulator Tab V=Insert Vinyl Sleeve R=Tape and Reel Q=3 <sup>rd</sup> Lead on Top P=3 <sup>rd</sup> Lead Ground G=Gull Wing J=Jacket B=Tape and Box X=Others, Pls Specify F=Lead Free	

### Tuning Fork Part Numbering System

ET ↓ Internal Code	DA	32.768	B	125	B	MB	L
Package	Nominal Frequency (In KHz)	Operation temperature Range	Load Capacitance	Frequency Tolerance	Marking	Option (can be blank)	
DA=DT-26 DB=DT-38 DC=DT-15 MB=SM308	Please enter the nominal frequency (6 digitals include the decimal)	A=0°C to +50°C B=-10°C to +60°C C=-10°C to +70°C D=-20°C to +70°C W=-40°C to +85°C	060=6.0pF 125=12.5pF 100=10pF (Pls enter the value of load capacitance)	A=±10ppm B=±20ppm C=±30ppm D=±50ppm E=±100ppm X=±5ppm Y=±15ppm Z=±25ppm	MP=With Marking MB=No Marking	L=Lead Cut R=Taping And Reel G=Gull Wing X=SpeCial SM=SMD Type F=Lead Free	

North American Sales & Distribution	 <p><b>Spectrum Component Sales, Inc.</b></p> <p>105 Hill Street, Suite 2D • Norcross, GA 30071 USA          TEL: 678-990-1754 • <b>TOLL FREE: 888-977-3287</b> • FAX: 678-990-1758          WEB: <a href="http://www.scsiglobal.com">www.scsiglobal.com</a> • EMAIL: <a href="mailto:sales@scsiglobal.com">sales@scsiglobal.com</a></p>
-------------------------------------	---

**TAIWAN:**

HOSONIC ELECTRONIC CO., LTD.  
 23-1 LANE 84. CHUN YING ST. SHULIN CHEN.  
 TAIPEI 23804. TAIWAN  
 WEB SITE:<http://www.hosonic.com.tw>

☎: 886-2-86875200  
 📠: 886-2-26816456  
 ✉: david@hosonic.com.tw

**CHINA:**

HANGZHOU HOSONIC ELECTRONIC CO., LTD.  
 NO.242 LIANGBO ROAD. LIANGZHU TOWN.  
 YUHANG DISTRICT, HANGZHOU, ZHEJIANG, CHINA  
 WEB SITE:<http://www.hosonic.com.cn>

☎: (86)-571-88778189  
 📠: (86)-571-88778857  
 ✉: market@hosonic.com.cn