microSpire

DESIGN SPECIFICATION DATA

Sales Engineer :
Reference :
Date :

Company Name : **Contact:**

Product PT-NR : **Project :** **Yearly Quantities :**

POWER TRANSFORMERS

Market : ☐ AIRSPACE ☐ AVIONICS / DEFENCE ☐ RAILWAY SYSTEMS
☐ Other : ☐ TELECOM ☐ INDUSTRY ☐ AUTOMOTIVE ☐ CONSUMER

Environment : Vibrations and/or shocks : Acceleration :
Humidity : Operating T° : Min/Max Storage T° : Min/Max

Applied Standards :

Power Supply Type : ☐ FORWARD ☐ PUSH PULL ☐ 50 / 400 Hz ☐ Other :

Output Inductor (µH) :

Primary Voltage / Duty Cycle : Ve Min / δ Max : Ve Max / δ Min :

Secondary Characteristics :

Output power range : Diode voltage drop : Working frequency :

Voltage / Current : ☐ AC ☐ DC Vs1 / Is1 : Vs2 / Is2 :
Vs3 / Is3 : Vs4 / Is4 :

Shield : Prim. / Sec. : Sec. / Sec. :

Isolation : Prim. / Sec. : Sec. / Sec. :
Windings / Shields : Windings / Ground :

Maximum Dimensions : Length : Width : Height :

Report Mode : ☐ SMD ☐ THROUGH-HOLE ☐ WIRES ☐ Other :

Finish : ☐ Box ☐ Gravity molding ☐ Transfer molding ☐ Coating
☐ None ☐ Dip impregnation ☐ Vacuum impregnation ☐ Injection

Marking : **Sticker on Packing :**

Packing : ☐ LOOSE ☐ STICK ☐ REEL ☐ TRAY ☐ UNITARY

MECHANICAL DRAWING

LAYOUT

IQ04/01/05a

Please return by fax this completely filled document at : +33.3.82.51.00.49